

# IC44821 (2120 mm/83' 7/16")



IC44821  
(2120 mm/83' 7/16")

**Easy-to-use electronic control panel, RABC compatible**

#### DIAMMS system

Automatic speed adjustment with moisture sensors to ensure a perfect result.

**Pressure roll with tightener springs, prevents wrinkling**

**Return feed, can be installed close to a wall for maximum space utilisation (LF model)**

**Labour saving automatic feeding and length-folding device (LF model)**

**Rear delivery (R model)**

#### Finger guard protection

Provides additional safety for operators.

**Durable ironing belts of Nomex withstand temperatures above 200°C**

**Nickel-plated cylinder prevents rust and improves lifetime.**

Rolls diameter, mm/in:	479/18' 14/16"
Ironing width, mm/in:	2120/83' 7/16"
Dimensions (widthxdepthxheight mm):	2785x1110x1270
Speed range, m/min:	1.5 to 9
Automatic Length Folding:	Option
Rear delivery:	Option
Automatic Feeding and Length Folding:	Option
Automatic Feeding and rear delivery:	Option

**Maintenance free ceramic gas burner**

Increases reliability for gas heated ironers

**Air circulation device on electric heated and stainless steel cylinder machines for an homogenous tempera-ture and an increased production****Options**

Multi-layer cylinder Dubixium™ for increased production on electric and gas heated machines  
CMIS, Certus Management Information System, connection for traceability according to European Standard EN14065

**Electrolux Professional North America, 3225 SW 42nd Street, Fort Lauderdale, Florida 33312 - Toll free: 866.449.4200**